

#10-R-2216840 109-D10602
1433741

SKID STEER WITH BUCKET AND COLD PLANNER TO MEET
THE FOLLOWING SPECIFICATIONS

This unit shall come with high-flow hydraulics which gives the unit the capacity to run various attachments to its maximum capacity and shall also have joy stick controls.

ENGINE:

Gross horsepower: 76 minimum
Net horsepower: 70 minimum
Aspiration: Turbocharged
Air Cleaner: Dry element
Fuel: Diesel

ELECTICAL SYSTEM
12 Volt

TRANSMISSION/STEERING

Type: Hydrostatic-Servo
Travel Speed: Two speed low 0-6 mph minimum
Two speed high 0-11 mph maximum

AXLES/TIRES/BRAKES

Axle: Oil bath lubrication of
inner and outer axle bearings (**PERMANENT SEALED**)
Brakes: Spring applied, hydraulically released wet-disk park brake
Tires: 12X16.5 brawler solid flex **OR EQUAL**

HYDRAULIC SYSTEM

Total pump flow with high-flow: 34 GPM minimum
High flow: 61 horsepower minimum

LOADER PERFORMANCE

Tipping Load: 5000 lb. minimum
Bucket breakout with heavy duty construction bucket: 5,300 lb minimum
SAE rated operating capacity: 2500 lbs minimum

DIMENSIONS

Dump height: 100 in. minimum
Dump reach with heavy-duty construction bucket: 41 in minimum
Ground clearance: 9 in. minimum

Dump angle (at full lift height) 45 degrees

THIS UNIT SHALL COME WITH THE FOLLOWING OPTIONAL
FEATURES

Four season cab with heater, defroster and air conditioner

Block heater

Transmission: 2 speed low

High-flow hydraulics

Backup alarm

Dual flashers

Handle Kit 8 button

Horn

Warning beacon Kit

Hand controls

Rear weight brackets

Bucket: 78" heavy duty construction

THIS SKID STEER MUST COME WITH A 1 YEAR FACTORY
WARRENTY PLUS A 4 YEAR ADDITIOINAL POWER
TRAIN/HYDRAULIC WARRENTY

COLD PLANER

This unit shall have fingertip, electrical control of tilt, depth, and side shift for positioning. This unit shall also have hinged access cover and have a one-year warranty.

Specifications:

Hydraulic flow rate: 29-41 gpm

Hydraulic pressure: 2,500-3500 psi

Hydraulic horsepower: 42-72 hp

Planing width: 24 in.

Planing depth: 0-5 in.

Tilt capability: Plus or minus 8 degrees

Side-shift capability: -3-22 in.

Number of carbide teeth: 57

Operating weight: 2,400 lb.